


# Hydraulic torque wrench pumps



*Sustainable Productivity*

**Atlas Copco**

<b>AIR-DRIVEN PUMPS</b>		<b>Panther A110</b>	<b>Panther A380</b>	<b>TigAir</b>
<b>Ordering Numbers</b>		Small Frame 8434 2040 19	8434 2056 22	8434 2059 62
		Full Frame 8434 2040 17		
<b>Dimensions (LxWxH)</b>	<b>inches</b>	13.4 x 13.7 x 16.5	15.7 x 14.9 x 18.1	18 x 10.5 x 18.5
	<b>mm</b>	340.3 x 347.9 x 419.1	398.7 x 378.4 x 459.7	457.2 x 266.7 x 439.9
<b>Weight</b>	<b>lb</b>	33	48	75
	<b>kg</b>	15	22	34
<b>Oil Capacity</b>	<b>Gallons</b>	0.5	1.5	2.5
	<b>Liters</b>	1.89	5.67	9.5
<b>Oil Flow@1250psi/86bar</b>	<b>cu.in</b>	275 cu.in/min	701 cu. in/min	-
	<b>l/min</b>	4.5 l/min	11.5 l/min	-
<b>Oil Flow@3600psi/250bar</b>		67 cu in./min	213 cu. in/min	-
		1.1 l/min	3.5 l/min	-
<b>Oil Flow@10,000psi/700bar</b>		24 cu. in/min	79 cu.in/min	72 cu. in/min
		0.4 l/min	1.3 l/min	1.1 l/min
<b>Ports</b>		1	4	1
<b>Recommended Tools</b>	RTP5	•	•	•
	RT1	•	•	•
	RT3	•	•	•
	RT5		•	•
	RT8		•	•
	RT10		•	•
	RT20		•	•
	RT25		•	•
	RT50		•	•
	RTX2	•	•	•
	RTX4		•	•
	RTX8		•	•
	RTX14		•	•
	RTX18		•	•
RTX30		•	•	

<b>ELECTRIC PUMPS</b>		<b>Panther 025</b>	<b>Panther 55</b>	<b>Lynx</b>	<b>Panther 150</b>
<b>Ordering Numbers</b>		110 V w/handle 8434 2040 31			
		110V w/full frame 8434 2040 33	110V 8434 2040 35	110V 8434 2059 61	110V 8434 2040 39
		220V w/handle 8434 2130 22	220V 8434 2040 37	220V 8434 2059 59	220V 8434 2040 41
		220V w/full frame 8434 2059 54			
<b>Dimensions (LxWxH)</b>	<b>inches</b>	12.6 x 8.3 x 15.3	17.3 x 9.4 x 18.5	9.5 x 17.14 x 18.12	18.11 x 11.81 x 17.33
	<b>mm</b>	320 x 210.8 x 388.6	439.4 x 238.7 x 469.9	541.3 x 435.3 x 460.2	460 x 300 x 440
<b>Weight</b>	<b>lb</b>	33	48	75	72
	<b>kg</b>	15	22	34	33
<b>Oil Capacity</b>	<b>Gallons</b>	0.5	1.5	2.5	1.5
	<b>Liters</b>	1.89	5.67	9.5	4.0
<b>Intercooler System</b>		No	Yes	Optional Accessory	Yes
<b>Oil Flow@ 1250psi/86bar</b>	<b>cu.in</b>	195 cu. in/min	391 cu. in/min	-	463 cu. in/min
	<b>l/min</b>	3.2 l/min	6.4 l/min	-	7.6 l/min
<b>Oil Flow@ 3600psi/250bar</b>		54 cu. in/min	110 cu. in/min	-	183 cu. in/min
		0.9 l/min	1.8 l/min	-	3.0 l/min
<b>Oil Flow@ 10,000psi/700bar</b>		21 cu. in/min	42 cu. in/min	56 cu. in/min	61 cu. in/min
		0.35 l/min	0.7 l/min	.9 l/min	1.0 l/min
<b>Ports</b>		1	4	1	4
<b>Recommended Tools</b>	RTP5	•	•	•	
	RT1	•	•	•	
	RT3	•	•	•	
	RT5		•	•	
	RT8		•	•	•
	RT10		•	•	•
	RT20		•	•	•
	RT25		•	•	•
	RT50		•	•	•
	RTX2	•	•	•	•
	RTX4		•	•	•
	RTX8		•	•	•
	RTX14		•	•	•
	RTX18		•	•	•
	RTX30		•	•	•

\* 4-port manifold is available as an optional accessory.  
Maintenance kits are available for every pump model. Consult your local Atlas Copco bolting representative for ordering information.

Electric Pumps can be ordered for use with 110V or 220V.

Air-driven pumps connect to a minimum 50psi power source.

**COMMITTED TO SUSTAINABLE PRODUCTIVITY**

[www.bolttighteningsolutions.com](http://www.bolttighteningsolutions.com)

